

## SAUNA DOOR INSTALLATION GUIDE

ATTENTION! PLEASE HANDLE AND INSTALL THE DOOR CAREFULLY, AS TEMPERED GLASS MAY SHATTER IF CORNERS AND EDGES COME INTO CONTACT WITH HARD SURFACES!



1. Place the door on a flat surface so the direction of the glass opening is facing upward. Next, one person holds the door by the glass in an open position, while the other person removes the edge guard used for shipping.  
If you want to change the direction of the door opening, the second person must move the lintel to the other side of the jambs.
2. To avoid breaking the glass during installation, place the door's wooden sticks on the floor of the doorway to provide a softer surface.
3. With one person holding the door glass in an open position and the other person holding the door by the jambs, carefully place the door in the doorway.
4. When installing the jambs use a level and, if required, adjust the position of the jambs with wedges. First, use screws to secure the jamb that is attached to the glass doorway. Then, by closing the glass door, it's possible to check the proper positioning of the other jambs in the doorway and ensure that the door can be closed freely.
5. Mount the horizontal crossbeams on the jamb, and seal the cracks between the jamb and the doorway with spray foam.
- 6a. If needed, the position of the glass can be adjusted by removing the hinge cover from the inside.
- 6b. Loosen the hinge bolts, adjust the glass to the desired position, then tighten the bolts to secure it.
7. The door kit includes a roller latch. If it's necessary to adjust the latch during installation, this can be done by adjusting the latch bolt so it works smoothly while the door remains tightly shut.

